T-778 P.002 F-472

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

Claim 1 (original): A system for evaluating or calibrating a bubble detector, comprising:

a conduit adapted to pass a flow material therethrough;

a pump operatively coupled to the conduit to pump the flow material through the conduit;

a bubble-forming device operatively coupled to the conduit, the bubble-forming device being adapted to introduce bubbles into the flow material passing through the conduit; and

a bubble detector to be evaluated positioned to examine the bubbles in the flow material passing through the conduit.

Claim 2 (currently amended): The system, as set forth in claim 1, comprising:

an elevation evaluation device positioned to examine the bubbles in the flow material passing through the conduit.

Claim 3 (original): The system, as set forth in claim I, wherein the pump comprises a peristaltic pump.

Claim 4 (original): The system, as set forth in claim 1, wherein the pump is capable of pumping the flow material through the conduit at a plurality of flow rates.

Claim 5 (original): The system, as set forth in claim 1, wherein the bubble-forming device comprises: a connecting device operatively coupled to the conduit;

Appl. No. 10/750,428 Amdr. Dated October 12, 2004 Reply to Office Action of July 13, 2004

a bubble-forming capillary adapted to be positioned within the connecting device in communication with the flow material passing through the conduit; and

a bubble-pumping device operatively coupled to the bubble-forming capillary, the bubble-pumping device adapted to deliver a bubble-forming material to the flow material in the conduit through the bubble-forming capillary to create bubbles in the flow material.

Claim 6 (original): The system, as set forth in claim 5, wherein the capillary comprises:

a proximal portion operatively coupled to the bubble-pumping device and a distal portion slidably positioned within the connecting device.

Claim 7 (original): The system, as set forth in claim 5, wherein the bubble-pumping device comprises a syringe.

Claim 8 (original): The system, as set forth in claim 5, wherein the bubble-pumping device is adapted to deliver the bubble-forming material at a plurality of bubble flow rates and sizes.

Claim 9 (currently amended): The system, as set forth in claim 1, comprising:

a pulse dampener operatively coupled the <u>conduit</u> lumen between the pump and the bubble-forming device.

Claim 10 (original): The system, as set forth in claim 1, wherein the flow material comprises a surfactant.

Claim I1 (original): The system, as set forth in claim 2, wherein the evaluation device comprises:

Appl. No. 10/750,428 Amdt. Dated October 12, 2004 Reply to Office Action of July 13, 2004

a previously evaluated bubble detector having a known bubble detection resolution.

Claim 12 (original): The system, as ser forth in claim 2, wherein the evaluation device comprises: an inspection device adapted to record bubbles formed by the bubble-forming device.

Claim 13 (currently amended): The system, as set forth in claim 12, wherein the inspection device comprises a camera operatively positioned proximate the connecting bubble-forming device.

Claim 14 (original): A method of evaluating or calibrating a bubble detector comprising the acts of:

- (a) pumping a flow material through a conduit;
- (b) introducing bubbles into the flow material;
- (c) examining the bubbles in the flow material with a bubble detector under evaluation; and
- (d) detecting the bubbles in the flow material.

Claim 15 (original): The method, as set forth in claim 14, wherein act (b) comprises the act of:
using a capillary to inject bubbles into the flow material.

Claim 16 (original): The method, as set forth in claim 15, wherein the act of using a capillary comprises the act of:

slidably positioning the capillary within the flow material to adjust the size of the bubbles.

Claim 17 (original): The method, as set forth in claim 15, wherein the acr of using a capillary comprises the acr of:

pumping a bubble-forming material through the capillary and into the flow material.

Appl. No. 10/750,428 Amdt. Dated October 12, 2004 Reply to Office Action of July 13, 2004

- Claim 18 (original): The method, as set forth in claim 14, wherein act (b) comprises the act of: introducing a gas into the flow material to create the bubbles.
- Claim 19 (original): The method, as set forth in claim 14, comprising the act of: mitigating pressure oscillations within the flow material.
- Claim 20 (original): The method, as set forth in claim 14, wherein act (c) comprises the act of:
  using an ultrasonic probe to examine the bubbles in the flow material at a plurality of ultrasonic signal levels.
- Claim 21 (original): The method, as set forth in claim 14, wherein act (d) comprises the act of: detecting the bubbles by visual inspection.
- Claim 22 (original): The method, as set forth in claim 14, wherein act (d) comprises the act of: detecting the bubbles using a bubble detector having a known bubble detection resolution.
- Claim 23 (original): The method, as set forth in claim 14, comprising the act of:

  comparing the examination of the bubbles in the flow material with the bubble detector with
  the detection of the bubbles in the flow material to calibrate the bubble detector.
- Claim 24 (original): The method of claim 23, comprising the acts of:
- (a) calculating a calibration factor from the examination of the bubbles in the flow material with the bubble detector and the detection of the bubbles in the flow material; and
  - (b) applying the calibration factor to the bubble detector to calibrate the bubble detector.

Appl. No. 10/750,428 Amdt. Dated October 12, 2004 Reply to Office Action of July 13, 2004

- Claim 25 (original): The method, as set forth in claim 14, wherein act (a) comprises the act of: pumping the flow material in the conduit at a plurality of flow rates.
- Claim 26 (original): The method, as set forth in claim 14, wherein act (b) comprises the act of: altering the size of the bubbles.
- Claim 27 (original): The method, as set forth in claim 14, wherein act (b) comprises the act of: altering a formation rate of the bubbles.
- Claim 28 (original): The method, as set forth in claim 24, wherein act (b) comprises the act of: programming the calibration factor into a memory of the bubble detector.

Claims 29-60 (cancelled)